







Memory-Efficient Searchable Symmetric Encryption


Angèle Bossuat, Raphael Bost, Pierre-Alain Fouque, Brice Minaud, Michael Reichle

ia.cr/2021/716

Roadmap

- Searchable Encryption: Introduction
- Problem statement: Page-efficient encryption.
- A solution: Tethys.

Outsourcing storage




Scenario: Client outsources storage of sensitive data to Server.

Examples:

- Company/hospital outsourcing client/patient info.
- Private email service.

Outsourcing storage




Scenario: Client outsources storage of sensitive data to Server.

Examples:

- Company/hospital outsourcing client/patient info.
- Private email service.

Sensitive data → encryption is needed.


Searchable Encryption



Searchable Encryption (SE):

- Client stores encrypted database on server.
- Client can perform search queries.
- Privacy of data and queries is desired.

Searchable Encryption




Searchable Encryption (SE):

- Client stores encrypted database on server.
- Client can perform search queries.
- Privacy of data and queries is desired.

Static SE: search queries.


Dynamic SE: search + update queries.

Searchable Encryption



Adversary: honest-but-curious server.

Security goal: privacy of data and queries.




Generic solutions (FHE) are infeasible at scale

→ for efficiency reasons, some leakage is allowed.

Example:

- Setup leaks: total number of elements in database.
- Search leaks: repetition of queries + IDs of documents matching each query.




Generic solutions (FHE) are infeasible at scale

→ for efficiency reasons, some leakage is allowed.

Example:

- Setup leaks: total number of elements in database.
- Search leaks: repetition of queries + IDs of documents matching each query.

Security model: Server learns nothing except leakage.



Generic solutions (FHE) are infeasible at scale

→ for efficiency reasons, some leakage is allowed.

Example:

- Setup leaks: total number of elements in database.
- Search leaks: repetition of queries + IDs of documents matching each query.

Security model: Server learns nothing except leakage.

No leakage about unqueried keywords.

State of the Art

No perfect solution.

Every solution is a trade-off between functionality and security.

Large amount of literature.

```
[AKSX04], [BCLO09], [PKV+14], [BLR+15], [NKW15], [KKNO16], [LW16], [FVY+17], [SDY+17], [DP17], [HLK18], [PVC18], [MPC+18]...
```

A few "complete" solutions:

Mylar (for web apps)

CryptDB (handles most of SQL)

→ Cipherbase (Microsoft), Encrypted BigQuery (Google), ...

State of the Art

No perfect solution.

Every solution is a trade-off between functionality and security.

Large amount of literature.

[AKSX04], [BCLO09], [PKV+14], [BLR+15], [NKW15], [KKNO16], [LW16], [FVY+17], [SDY+17], [DP17], [HLK18], [PVC18], [MPC+18]...

A few "complete" solutions:

Mylar (for web apps)

CryptDB (handles most of SQL)

Very controversial security

→ Cipherbase (Microsoft), Encrypted BigQuery (Google), ...

State of the Art

No perfect solution.

Every solution is a trade-off between functionality and security.

Large amount of literature.

```
[AKSX04], [BCLO09], [PKV+14], [BLR+15], [NKW15], [KKNO16], [LW16], [FVY+17], [SDY+17], [DP17], [HLK18], [PVC18], [MPC+18]...
```

A few "complete" solutions:

Mylar (for web apps)

CryptDB (handles most of SQL)

Very controversial security

→ Cipherbase (Microsoft), Encrypted BigQuery (Google), ...

Today: single-keyword SSE.

Single-keyword SSE










Reverse index:

"car" \mapsto id₁, id₃


"duck" \mapsto id₂, id₃, id₆, ...

...

Single-keyword SSE



Single-keyword SSE: Setup



Legend:




Encrypted reverse index:







Encrypted reverse index:















Encrypted reverse index:













Naive solutions for list storage:




Naive solutions for list storage:




Leaks lengths of all keywords.




Naive solutions for list storage:






Naive solutions for list storage:



Position of one list depends on lengths of other lists.





Database 1

Database 2


Client queries:


Database 1 Database 2 Client queries: **Server view:** Database 1 Database 2







Server memory








Server memory



Server memory




Security: OK.

List of length $\ell = \ell$ unif. random memory accesses

Secure list storage

Server memory




Security: OK.

List of length $\ell = \ell$ unif. random memory accesses

Efficiency: Terrible.

Secure list storage

Server memory



Security: OK.

List of length $\ell = \ell$ unif. random memory accesses

Efficiency: Terrible.

Worst-case cost for Hard Disk Drives: reading contiguous memory much cheaper than random locations.

Cash & Tessaro EC '14

Cash & Tessaro EC '14

Locality: #discontinuous memory accesses to answer a query.

Cash & Tessaro EC '14

Locality: #discontinuous memory accesses to answer a query.

Read efficiency: #memory words accessed to answer a query / #memory words of plaintext answer.

Cash & Tessaro EC '14

Locality: #discontinuous memory accesses to answer a query.

Read efficiency: #memory words accessed to answer a query / #memory words of plaintext answer.

Storage efficiency: #memory words to store encrypted DB / #memory words of plaintext DB.

Cash & Tessaro EC '14

Locality: #discontinuous memory accesses to answer a query.

Read efficiency: #memory words accessed to answer a query / #memory words of plaintext answer.

Storage efficiency: #memory words to store encrypted DB / #memory words of plaintext DB.

Theorem (Cash & Tessaro EC'14):

Secure SSE cannot have O(1) in all 3 measures.

Building local SSE

Asharov et al. STOC '16

N = size of DB

Scheme	Locality	Storage eff.	Read eff.
"One-choice"	O(1)	O(1)	Õ(log N)
"Two-choice"	O(1)	O(1)	Õ(log log N)*
"Pad-and-split"	O(1)	O(log N)	O(1)

Demertzis et al. Crypto '18

Scheme	Locality	Storage eff.	Read eff.
Untitled	O(1)	O(1)	$O(log^{2/3+\epsilon} N)$

- - -

^{*}under condition: longest list size ≤ N¹-¹/log log N

HDD vs SSD

Two most prevalent media for storage:








Solid State Drive (SSD, "Flash")

HDD vs SSD



SSDs Outsell HDDs in Unit Sales 3:2: 99 Million Vs. 64 Million in Q1

By Anton Shilov May 21, 2021

But HDDs maintain exabytes lead: 288.3EB vs 61.5EB.

HDD: locality (+ read efficiency).

HDD: locality (+ read efficiency).

SSD: locality does not matter...

HDD: locality (+ read efficiency).

SSD: locality does not matter...

What matters: number of memory pages read.

HDD: locality (+ read efficiency).

SSD: locality does not matter...


What matters: number of memory pages read.

Server memory

HDD: locality (+ read efficiency).

SSD: locality does not matter...


What matters: number of memory pages read.



HDD: locality (+ read efficiency).

SSD: locality does not matter...

What matters: number of memory pages read.



HDD: Locality + Read efficiency + Storage efficiency.

SSD:

Page efficiency: #memory pages accessed to answer a query / #memory pages of plaintext answer.

Storage efficiency: #memory words to store encrypted DB / #memory words of plaintext DB.


HDD: Locality + Read efficiency + Storage efficiency.

SSD:

Page efficiency: #memory pages accessed to answer a query / #memory pages of plaintext answer.

Storage efficiency: #memory words to store encrypted DB / #memory words of plaintext DB.

Throughput of asynchronous reads, function of the block size



HDD: Locality + Read efficiency + Storage efficiency.

Theorem (Cash & Tessaro EC '14):

Secure SSE cannot have O(1) in all 3 measures.

HDD: Locality + Read efficiency + Storage efficiency.

Theorem (Cash & Tessaro EC '14):

Secure SSE cannot have O(1) in all 3 measures.

SSD: Page efficiency + Storage efficiency.

Can we get O(1) in both measures?

HDD: Locality + Read efficiency + Storage efficiency.

Theorem (Cash & Tessaro EC '14):

Secure SSE cannot have O(1) in all 3 measures.


SSD: Page efficiency + Storage efficiency.

Can we get O(1) in both measures?

(Yes.)

Page-efficient allocation


Problem recap



Problem recap Lists store Server memory One page (+ Stash)

WLOG all lists are of size at most one page:





WLOG all lists are of size at most one page:



Problem recap Lists Server memory One page + Stash

Goal:

Page efficiency: #pages accessed to get one list = O(1).

Storage efficiency: # pages to store encrypted DB = O(n).

Data-Independent Packing Lists Server memory

Goal:

+ Stash

Page efficiency: #pages accessed to get one list = O(1).


Storage efficiency: # pages to store encrypted DB = O(n).

Security: pages accessed to get list ID = $f_n(ID)$. Does not depend on rest of DB.


One page











+ Stash














Invariant:

Every list ⊆ its two associated buckets + the stash.


+ Stash















































































Tethys Lists **x**1 **x**5 **x**3 **x**4 Server memory each page overflow = 1 vertex



Tethys





Tethys Lists **x**5 **x**1 **x**4 each item = 1 edge Server memory each page overflow = 1 vertex

Goal of algorithm: find maximal set of disjoint paths from overfull pages to underfull pages.


Tethys Lists **x**5 **x**1 **x**4 each item = 1 edgeServer memory each page overflow = 1 vertex

Goal of algorithm: find maximal set of disjoint paths from overfull pages to underfull pages.

This is exactly a maximum flow algorithm.

+ Stash


Tethys summary



Tethys allocation


- 1. Assign 2 unif. random pages to each list.
- 2. Put each list in one of the two pages (arbitrarily).
- 3. Compute max flow over graph to find set of paths.
- 4. Move items along paths.
- 5. Items that still overflow, if any, go to the stash.

Optimization problem



Objective: minimize stash size under constraint: all items are assigned somewhere, no page overflows.

Optimization problem



Objective: minimize stash size under constraint: all items are assigned somewhere, no page overflows.

Tethys is **optimal** wrt this optimization problem.

i.e. outputs minimal stash size regardless of starting graph.

What size is the stash?

Parameter choice

Let $n = \Sigma$ list sizes/p = #pages in DB.

Let s = #pages in stash.

Pick $m = (2 + \varepsilon)n$ pages for server memory, for any cst $\varepsilon > 0$.

Theorem

For **any** set of lists (s.t. $n = \Sigma$ list sizes/p):

Prob[min stash size > s] = O(n-s/2)

What size is the stash?

Parameter choice

Let $n = \Sigma$ list sizes/p = #pages in DB.

Let s = #pages in stash.

Pick $m = (2 + \varepsilon)n$ pages for server memory, for any cst $\varepsilon > 0$.

Theorem

For **any** set of lists (s.t. $n = \Sigma$ list sizes/p):

Prob[min stash size > s] = O(n-s/2)

 \rightarrow stash size $\omega(\log \lambda)/\log n \Rightarrow$ prob of failure is negligible.

Stash is stored on the client side.

Does not grow with the size of the database.

Experiments: a few pages suffice.

Let L be a multiset of list sizes s.t. $\Sigma L = np$.

Let M be the multiset $\{p,p,p,\dots\}$ s.t. $\Sigma M = np$.

Central statement (simplified):


 $Prob[minStash(L) > s] \le Prob[minStash(M) > s]$

Let L be a multiset of list sizes s.t. $\Sigma L = np$.

Let M be the multiset $\{p,p,p,\dots\}$ s.t. $\Sigma M = np$.

Central statement (simplified):

 $Prob[minStash(L) > s] \le Prob[minStash(M) > s]$




Let L be a multiset of list sizes s.t. $\Sigma L = np$.

Let M be the multiset $\{p,p,p,\dots\}$ s.t. $\Sigma M = np$.

Central statement (simplified):

 $Prob[minStash(L) > s] \le Prob[minStash(M) > s]$




Let L be a multiset of list sizes s.t. $\Sigma L = np$.


Let M be the multiset $\{p,p,p,\dots\}$ s.t. $\Sigma M = np$.


Central statement (simplified):


 $Prob[minStash(L) > s] \le Prob[minStash(M) > s]$





This is cuckoo hashing!



























Performance:

Page efficiency: #pages accessed to get one list

Storage efficiency: #pages to store encrypted DB / n

Client storage: $\omega(\log \lambda)/\log n$ pages.




Performance:

Page efficiency: # pages accessed to get one list = 2 (+1)

Storage efficiency: #pages to store encrypted DB / n

Client storage: $\omega(\log \lambda)/\log n$ pages.



Performance:

Page efficiency: # pages accessed to get one list = 2 (+1)

Storage efficiency: #pages to store encrypted DB / $n = 2+\epsilon$

Client storage: $\omega(\log \lambda)/\log n$ pages.

Performance evaluation

Theory


Schemes	Client st.	Page eff.	Storage eff.
$\Pi_{ m bas}$	$\mathcal{O}(1)$	$\mathcal{O}(p)$	$\mathcal{O}(1)$
$\Pi_{ m pack}, \Pi_{ m 2lev}$	$\mathcal{O}(1)$	$\mathcal{O}(1)$	$\mathcal{O}(p)$
1-Choice	$\mathcal{O}(1)$	$\widetilde{\mathcal{O}}(\log N)$	$\mathcal{O}(1)$
2-Choice	$\mathcal{O}(1)$	$\widetilde{\mathcal{O}}(\log\log N)$	$\mathcal{O}(1)$
Tethys	$\mathcal{O}(p\log\lambda)$	3	$3+\varepsilon$
Pluto	$\mathcal{O}(p\log\lambda)$	3	$3+\varepsilon$
$Nilus_t$	$\mathcal{O}(p\log\lambda)$	2t+1	$1 + (2/e)^{t-1}$

Performance evaluation

Theory

Schemes	Client st.	Page eff.	Storage eff.
$\Pi_{ m bas}$	$\mathcal{O}(1)$	$\mathcal{O}(p)$	$\mathcal{O}(1)$
$\Pi_{ m pack}, \Pi_{ m 2lev}$	$\mathcal{O}(1)$	$\mathcal{O}(1)$	$\mathcal{O}(p)$
1-Choice	$\mathcal{O}(1)$	$\widetilde{\mathcal{O}}(\log N)$	$\mathcal{O}(1)$
2-Choice	$\mathcal{O}(1)$	$\widetilde{\mathcal{O}}(\log\log N)$	$\mathcal{O}(1)$
Tethys	$\mathcal{O}(p\log\lambda)$	3	$3+\varepsilon$
Pluto	$\mathcal{O}(p\log\lambda)$	3	$3+\varepsilon$
$Nilus_t$	$\mathcal{O}(p\log\lambda)$	2t+1	$1 + (2/e)^{t-1}$

Implementation



THANKS

Questions?